



## Breakers

Pound for pound, blow for blow, the JCB range of breakers is the best for demolition and breaking work. They'll power their way through most jobs.

Thanks to their excellent power-to-weight ratio, our breakers will give amongst the best performance of any type of breaker in their class.

### Features

- Vibro damped handles which give amongst the lowest vibration levels of any equivalent breaker
- Sealed hydraulic system resulting in low noise (no exhaust port) and elimination of freezing problems
- Very robust cast steel construction for maximum strength and durability
- High reliability and long service life, thanks to only having two moving parts and constant lubrication by hydraulic oil



**D-Pick**

Light demolition and construction applications.  
Ideal for trenching, tunnelling and lateral work.

**Details**

Model name	D Pick	
Model number	929/30800 (Latch retainer) 929/12900 (Screw retainer)	
Weight	kg (lb)	15 (33)
Tool / chisel size hex	mm (in)	22 (7/8)
Hydraulic flow	l/min (gal/min)	15-22 (3-5)
Pressure range	Bar (psi)	50-65 (725-942)
Blow frequency	blows/min	1500
Vibration (BS8622-5)	m/s <sup>2</sup>	6
Sound power level	dB L <sub>wa</sub>	106

**T-Pick**

Small lightweight hammer designed for light to medium-duty breaking.

**Details**

Model name	T Pick	
Model number	929/30900	
Weight	kg (lb)	15 (33)
Tool / chisel size hex	mm (in)	22 (7/8)
Hydraulic flow	l/min (gal/min)	15-22 (3-5)
Pressure range	Bar (psi)	50-65 (725-942)
Blow frequency	blows/min	1500
Vibration (BS8622-5)	m/s <sup>2</sup>	7.5
Sound power level	dB L <sub>wa</sub>	106

**HM22**

Medium-duty breaker for general demolition, concrete and asphalt breaking.

**Details**

Model name	HM22	
Model number	929/92600 (25mm (1") Chisel) 929/92500 (22mm (5/8") Chisel)	
Weight	kg (lb)	21 (46)
Tool / chisel size hex	mm (in)	22 (1 1/8) or 25 (1)
Hydraulic flow	l/min (gal/min)	15-22 (3-5)
Pressure range	Bar (psi)	50-65 (725-942)
Blow frequency	blows/min	1500
Vibration (BS8622-5)	m/s <sup>2</sup>	3.4
Sound power level	dB Lwa	106

**HM25**

Reinforced concrete, heavy roadwork's, asphalt and high output applications.

**Details**

Model name	HM25	
Model number	929/92400	
Weight	kg (lb)	26 (57)
Tool / chisel size hex	mm (in)	32 (1 1/4)
Hydraulic flow	l/min (gal/min)	18-22 (4-5)
Pressure range	Bar (psi)	90-110 (1305-1595)
Blow frequency	blows/min	1500
Vibration (BS8622-5)	m/s <sup>2</sup>	4
Sound power level	dB Lwa	108



**HM25LV**

The HM25LV breaker when used with the Beaver Powerpack gives the ultimate in terms of performance and ultra low hand arm vibration levels. Unique JCB patented active hydraulic suspension dispenses of traditional springs and bushes to give single axis vibration of  $1.6\text{m/s}^2$ .

**Details**

Model name	HM25LV	
Model number	929/A2613	
Weight	kg (lb)	27 (60)
Tool / chisel size hex	mm (in)	32 (1 1/4)
Hydraulic flow	l/min (gal/min)	18-22 (4-5)
Pressure range	Bar (psi)	90-110 (1305-1595)
Blow frequency	blows/min	1500
Vibration (BS8622-5)	$\text{m/s}^2$	1.6
Sound power level	dB L <sub>WA</sub>	108

